

Ruby lavatory faucet MX10






Ruby lavatory faucet MX10, with IR-Sensor, with temperature mixing, chrome

Touch-free, electronically controlled lavatory faucet:

- modular two-piece construction
- sturdy metal housing (polished)
- dual infrared sensors with automatic setting feature, microprocessor-electronic
- reliable magnetic valve and economy aerator
- water supply connection with flexible high-pressure hoses and filters (built in)
- temporary-off (cleaning) can be activated through "Touch"
- continuous water flow time (filling of basin) can be activated / adjusted through "Touch"
- water follow-up time and sensor sensitivity adjustable through "Touch"
- 24-hour hygienic rinse can be activated through "Touch"
- installation like conventional single-lever faucet

Touch: setting the sensor or features, by touching the sensor
 Battery: 6V Lithium CRP 2 - life time up to 4 years
 Mains operation: plug-in transformer 100-250VAC / 6VDC
 VARIOconnect: single / multiple power supply, see accessories



Description	power supply	Code
Ruby lavatory faucet MX10, with IR-Sensor, with temperature mixing, chrome		132.000.11
		132.010.11
	prepared for mains power supplies (accessories)	132.016.11

Technical data:

Operating pressure: 0,3 - 10 bar
 Flow rate: approx. 5 l/min. (3 bar)
 Max. water temperature: 80° C
 Aerator: economy aerator, cascade (self-cleaning)
 Flexible hose: 35 cm
 Angle valve connection: G 3/8"
 Filter: 0,5 mm mesh size
 Sensor-sensitivity: automatic self-adapting sensor technology
 Follow-up time: 1 sec. pre-set (adjustable with Touch 0-10 sec.)
 Continuous water flow and hygienic rinse time: 2 min. pre-set (adjustable with Touch 0,5 - 20 min.)
 Temporary-off: 2 min. (fixed)
 Engineering standards: DIN EN 200; noise class I; P-IX 9575 / IA; 