
P RF GLOBE 60 6 W/827 E27 FIL

PARATHOM Retrofit CLASSIC GLOBE | LED lamps, classic ball shape



Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires
- Perfect for decorative installations

Product benefits

- Clear lamps with innovative LED "filament" technology
- Very low energy consumption
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs

Product features

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Lifetime: up to 15,000 h
- Beam angle: up to 360°
- Energy efficiency class: A++



Technical data

Electrical data

| | |
|--|-------------|
| Rated wattage | 6.00 W |
| Nominal wattage | 6.00 W |
| Nominal voltage | 220...240 V |
| Operating frequency | 50...60 Hz |
| Power factor λ | > 0.50 |
| Claimed equiv. conventional lamp power | 60 W |


Photometrical data

| | |
|---|---------------|
| Nominal luminous flux | 806 lm |
| Rated luminous flux | 806 lm |
| Color temperature | 2700 K |
| Color rendering index Ra | ≥ 80 |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Standard deviation of color matching | ≤ 6 sdcn |

Light technical data

| | |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & weight



| | |
|----------------|----------|
| Overall length | 168.0 mm |
| Diameter | 124.0 mm |
| Outer bulb | G125 |
| Length | 168.0 mm |

Product datasheet

Lifespan

| | |
|--|---------|
| Nominal lamp life time | 15000 h |
| Rated lamp life time | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service life | 0.70 |

Additional product data

| | |
|-----------------------------------|--|
| Base (standard designation) | E27 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |
| Appropriate disposal acc. to WEEE | Yes |
| Product remark | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & standards

| | |
|-------------------------|-------------|
| Energy efficiency class | A++ |
| Energy consumption | 6 kWh/1000h |

Country specific categorizations

| | |
|-----------------|------------------------------|
| ILCOS | DRAG/C-6/827-220-240-E27-124 |
| Order reference | PRFCLG125606W/8 |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|----------------------------------|---------------------------------|---|-----------------------|--------------|
| 4052899972773 | P RF GLOBE 60 6 W/827 E27 FIL | Shipping carton box 10 | 710 mm x 290 mm x 366 mm | 75.36 dm ³ | 1616.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Product datasheet

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.