# PRODUCT DATASHEET SMART+ WiFi Spot 50 45 ° 4.9 W/2700...6500 K GU10

SMART+ WiFi SPOT GU10 Multicolour | Reflector shape with WiFi technology

### Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor applications only in suitable luminaires

### **Product benefits**

- Wireless control via app
- Easy to install and use
- Contains no mercury

### **Product features**

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android 4.4 or iOS 9.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi
- Lifetime: up to 20,000 h






## **TECHNICAL DATA**

## Electrical data

Nominal wattage	4.9 W
Construction wattage	4.90 W
Nominal voltage	230 V
Nominal current	45 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	50 W

### Photometrical data


Light color (designation)	RGBW
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	≤5 sdcm
Nominal luminous flux	350 lm
Luminous flux	350 lm
Luminous efficacy	71 lm/W
Luminous intensity	467 cd
Adjustable color temperature	27006500 K
Color temperature	27006500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.9



# Light technical data

Beam angle	45 °
Starting time	< 0.5 s

# Dimensions & Weight



Product weight	53.00 g
Diameter	50.00 mm
Length	52.00 mm
Width	50.00 mm
Height	50.00 mm
Outer bulb [PICOS]	PAR51

# Lifespan

Lifespan	20000 h
Lumen maintenance at end of serv	0.70

### Colors & materials

Housing color	White

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C

### Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	GU10

# **Capabilities**

Dimmable	Yes
Compatible smart home technology	Google Assistant / Amazon Alexa

### Certificates & Standards

Energy efficiency class	G <sup>1)</sup>
Energy consumption	5.00 kWh/1000h
Standards	CE
Type of protection	IP20

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Energy labellling regulation data acc EU 2019/2015

Lighting technology used  Non-directional or directional  Mains or non-mains  MLS  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  No  High luminance light source  No  Anti-glare shield  No
Light source cap-type (or other electric interface)  Connected light source (CLS)  yes  Color-tuneable light source  yes  Envelope  No  High luminance light source  No
Connected light source (CLS)  Color-tuneable light source  yes  Envelope  No  High luminance light source  No
Color-tuneable light source yes  Envelope No  High luminance light source No
Envelope No High luminance light source No
High luminance light source No
Anti-glare shield No
Correlated colour temperature type RANGE
Claim of equivalent power Yes
Chromaticity coordinate x 0.461
Chromaticity coordinate y 0.420
R9 Colour rendering index 0.00
Beam angle NARROW_CONE_90
LED light source replaces a fluorescent light source not applicable
EPREL ID 528214,528214
Model number AC33927,AC33927

### **DOWNLOAD DATA**

	DOWNLOAD DATA
PDF	Declarations of conformity EC Declaration of Conformity SMART+ WIFI PAR16 R50 R63 HS
PDF	Installation guide SMART+ WIFI INSTALLATION GUIDE

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075485693	Folding box 1	61 mm x 78 mm x 96 mm	134.00 g	0.46 dm <sup>3</sup>
4058075485709	Shipping box 4	173 mm x 108 mm x 141 mm	625.00 g	2.63 dm <sup>3</sup>
4058075521476	Shipping box 32	359 mm x 229 mm x 303 mm	3984.00 g	24.91 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.