

- LED recessed spotlight with aluminium housing and spring mounting clips
- High performance replacement for halogen spotlights
- 30° tilting angle
- Dimmable
- Lifetime of 30,000 hrs



**Order Code** 52405

#### General Data

Type of Installation	Recessed
Housing Material	Aluminum
Housing Color	White
Protection Class	IP20

#### Geometric Data

Height (mm)	55
Outer Diameter (mm)	112
Inner Diameter (mm)	75
Weight (g)	360

#### Electric Data

Wattage (W)	12.0
Voltage (V)	220-240 / ext. driver
Power Factor	0.90
Operating Frequency (Hz)	50-60
Safety Class	II

#### Photometric Data

Luminous Flux (lm)	710
Luminous Flux 90° (lm)	675
CRI	≥ 80
CCT (K)	3000
Luminous Efficiency (lm/W)	59
Luminous Intensity (cd)	1200
Beam Angle (°)	40

#### Lifespan

Lifetime (hrs)	30,000
Switching Cycle	60,000

**Dimmability** Yes

**Energy Efficiency Class** A





<b>Order Code</b>	52405
<b>Product Description</b>	LED Downlight 12W 3000K ww 675lm 40° White DIM

### Technical Packaging Details

Barcode	023942524052
EAN 128	(02)00023942524052(37)04(91)162
EAN 14	50023942524057
Pack Dimensions (HxWxL)	168 mm x 120 mm x 73 mm
Pack Weight	450
Carton Qty (Shipping Unit)	4
Carton Dimensions (HxWxL)	352 mm x 250 mm x 95 mm
Cartons/Pallet	90
Layers/Pallet	10
Units/Pallet	360

## Photometric Diagram

52405

