

DALI Driver for 500mm LED Ceiling Light

- Tridonic LED DALI Driver for 500mm LED Ceiling Light
- Code: TRIDONIC LCA 45W 500-1400mA one4all C PRE
- Power Factor $\geq 0,9$
- DALI dimmable
- DSI
- SwitchDIM and corridorFunction



Order Code	52935
General Data	
Primary Voltage Range (V)	200-240
Frequenzy (Hz)	50/60
Input current (A)	0.2
Output current (A)	0.87
Secondary Voltage (V)	60V max. (36V with Verbatim LED Ceiling Light)
Power Factor	0.95
Ambient Temperature t_a (°C)	-25 to 50
Max Case Temperature t_c (°C)	95
Dimming	DALI
Dimensions LxWxH (mm)	120 x 70 x 23
Protection Class	IP20
Weight (g)	160
Primary Terminal	2-pole, pre-wired with dedicated connector
Secondary Terminal	2-pole, pre-wired with dedicated connector
Standards	EN61347-1
	EN61347-2-13
	EN61000-3-2
	EN61000-3-3
	EN55015
	EN61547
	EN62384
	EN62386-101
	/-102/-207



Updated June 2018

www.verbatimlighting.com

DALI Driver for 500mm LED Ceiling Light

Order Code	52935
Product Description	Tridonic LED DALI Driver for 500mm LED Ceiling Light

Technical Packaging Details

Barcode	023942529354
Outer EAN 14	50023942529359
Outer EAN 128	(02)00023942529354(37)20(91)52
Pack Dimensions (HxWxL)	48mm x 73mm x 150mm
Pack Weight (g)	180
Carton Qty (Shipping Unit)	1
Layers/Pallet	5
Units/Pallet	900